

PERFORMANCE FLUIDS

TYPICAL DATA SHEET

Effective: as from December 01, 2011

Varsol™ 40

Hydrocarbon Fluid

Property	Units	Method	Typical values Antwerp production
Aniline point	°C	ASTM D 611	54
Aromatic content	wt%	GC1	21
Benzene content	mg/kg	GC2	44
Colour, Saybolt	-	ASTM D 6045	+30
Density at 15°C	kg/dm ³	ISO 12185	0.789
Distillation range	°C	ASTM D 86	
Initial Boiling Point			157
50% Boiling Point			173
Dry Point			193
Evaporation rate (n-BuAc = 100)	-	EC-M-F01	13
Flash point	°C	ASTM D 56	42
Refractive index at 20°C	-	ASTM D 1218	1.440
Sulphur content	mg/kg	ASTM D 5453	<1

The values stated on this Typical Data sheet represent only the typical values for the mentioned properties as per ExxonMobil reporting rules. These are not the product's specifications for which you should refer to the Sales Specification sheet.

Values may be determined by one or more ExxonMobil test methods equivalent to industry standard test methods. Applicable sampling and testing methods are subject to change without notice and are available for review on request.

The values indicated in this document may deviate from the test method requirements by the number of significant figures shown.

©2011 Exxon Mobil Corporation. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly steward. ExxonMobil, The ExxonMobil Emblem, the "Interlocking X" Device, Escaid, Exx-Print, Exxsol, Han, Isopar, Nappar, Somentor, Varsol and Solvesso are trademarks of Exxon Mobil Corporation.